



A-400AD SERIES



Product Details:

Features:

- Low profile, less weight
- High reliability, strong load capability
- Protections: Overload/Short circuit
- 100% pass full load high temp aging test
- Size: 217×117×30mm

AC Input Voltage Range/Input Frequency.....	180~264VAC/47~63Hz
AC Inrush Current.....	cold start, 100A/230VAC
Line Regulation(full load).....	
±1%	
Output Overload Protection.....	110%-150% Hiccup mode,auto-recover
Rise, Hold up time.....	100mS, 10mS at full load
Withstand Voltage.....	I/P-O/P:3KVAC,I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC,1 min
Working temperature.....	-30~+60refer to temperature derating curve)
Storage Temperature.....	-40~+100, 20~95%RH(non-condensing)
Safety Standards.....	GB4943, UL60950-1, EN60950-1
EMC Standards.....	GB9254, EN55022 class A
Cooling Method.....	Forced air cooling by built-in DC fan



Model No	DC output	Tol	R&N	Effi.
A-400AD-2.8	2.8V, 0~80A	±2%	150mV	78%
A-400AD-3.3	3.3V, 0~80A	±2%	150mV	80%
A-400AD-3.8	3.8V, 0~80A	±2%	150mV	81.5%
A-400AD-4.2	4.2V, 0~80A	±2%	150mV	83%
A-400AD-5	5V, 0~80A	±2%	150mV	84%

